

# OSCILLOSCOPES

## Digitizing Oscilloscopes

HP 54502A

### HP 54502A 400 MHz, 400 MSa/s Digitizing Oscilloscope

The HP 54502A is a 400 MHz, 400 MSa/s sample rate, 2-channel digitizing oscilloscope designed for both repetitive and single-shot signals. In repetitive mode, the HP 54502A has a 400 MHz bandwidth. In real-time mode, its 400 MSa/s sample rate provides a single-shot bandwidth of 100 MHz. Like other members of the HP 54500 family, the HP 54502A has all the digitizing advantages of oscilloscopes that are much higher in price. Its high repetitive/single-shot bandwidth, ease of use, HP-IB programmability, and HP 54500 family general-purpose features make it a powerful tool for both manual and automated test applications.

### HP 54502A Specifications and Characteristics

	Real-Time	Repetitive
<b>Bandwidth</b> (-3 dB) dc-coupled	dc to 100 MHz	dc to 400 MHz <sup>a</sup>
<b>Switchable bandwidth limits</b>	ac-coupled lower -3 dB freq.: 10 Hz LF reject lower -3 dB freq.: 450 Hz Bandwidth limit: dc to 30 MHz	
<b>Rise time<sup>2</sup></b>	3.5 ns	875 ps
<b>Number of channels</b>	2 (simultaneous)	
<b>Vertical sensitivity range</b>	2 mV/div to 5 V/div	
<b>Vertical gain accuracy (dc)<sup>3,4</sup></b>	±2.0% of full scale	
<b>Vertical resolution<sup>4</sup></b>	±1.6% of full scale (8 bit A/D) ±0.4% of full scale (8 bits with ≥ 8 averages)	
<b>Maximum sample rate</b>	400 MSa/s	25 MSa/s
<b>Waveform record length<sup>5</sup></b>	Normal: 501 points Extended: 2001 points	Time/div 5 ns to 5 s/div 2 ns/div 1 ns/div Rec length 501 pts 401 pts 201 pts
<b>Input R (selectable)</b>	1 MΩ ±1% or 50 Ω ±1%	
<b>Input C</b>	7 pF nominal	
<b>Input coupling</b>	ac, dc	
<b>Maximum input voltage</b>	1 MΩ: ±250 V [dc + peak ac (< 10 kHz)] 50 Ω: 5 V rms	
<b>Offset range</b>	Vertical sensitivity: 2 mV to 50 mV/div > 50 mV to 250 mV/div > 250 mV to 1.25 V/div > 1.25 V to 5V/div	Available offset: ±2 V ±10 V ±50 V ±250 V
<b>Offset accuracy<sup>6</sup></b>	±(2 mV + 2% of ch. offset + 2.5% of full scale)	
<b>Dynamic range</b>	±1.5 × full scale from center of screen	
<b>Channel-to-channel isolation</b>	40 dB: dc to 50 MHz 30 dB: 50 to 100 MHz (with channels at equal sensitivity)	40 dB: dc to 50 MHz 30 dB: 50 to 400 MHz
<b>Voltage measurement accuracy (dc)<sup>3,4</sup></b>	Dual cursor: ±(2.0% of full scale + 0.032 × V/div) Single cursor: ±(2.0% of full scale + offset accuracy + 0.016 × V/div)	
<b>Time base range</b>	1 ns/div to 5 s/div	
<b>Time base reference accuracy</b>	0.01%	
<b>Maximum time base resolution</b>	50 ps (maximum)	
<b>Delta-t accuracy</b>	±(2% × screen diameter + 0.01% × delta t + 500 ps)	±(2% × screen diameter + 0.01% × delta t + 250 ps)
<b>Delay range (post-trigger)</b>	Time/div setting: 50 ms to 5 s/div 100 μs to 20 ms/div 1 ns to 50 μs/div	Available delay: 40 × (s/div) 1s 10 000 × (s/div)

	Real-Time	Repetitive	
<b>Delay range (pre-trigger)</b>	All time/div settings: 40 × (s/div)	Time/div setting: 1 μs to 5 s/div 10 ns to 500 ns/div 1 ns to 5 ns/div	Available delay: -40 × (s/div) -80 μs -10 000 × (s/div)
<b>Internal trigger coupling</b>	Line trigger Low-frequency reject (-3dB 50 KHz)		
<b>Trigger sensitivity<sup>7</sup></b>	Internal dc to 100 MHz 100 MHz to 400 MHz External dc to 250 MHz		
	0.5 div N/A 100 mV peak-to-peak into 50 Ω	0.5 div 1.25 div	
<b>Trigger pulse width (minimum):</b>	Internal: 7.0 ns External: 2.8 ns		
<b>Trigger level range</b>	Internal: ±1.5 × full scale from center of screen External: ±2V		

**Power requirements:** Voltage: 115/230 Vac, -25% to +15% 48 to 66 Hz. Power 350 VA maximum.

**Weight:** Net: approximately 10 kg (22 lb). Shipping: approximately 20 kg (44 lb).

**Size:** 194.3 mm H × 422.3 mm W × 355.6 mm D (7.65 in × 16.62 in × 14 in); does not include front panel protrusions.

Specifications valid for temperature range ±10° C from software calibration temperature with 8 or more averages selected.

<sup>1</sup>Upper bandwidth reduces by 2.5 MHz for each °C above +35° C.

<sup>2</sup>Rise times are calculated from:

$$t_r = \frac{0.35}{\text{bandwidth}}$$

<sup>3</sup>Vertical gain accuracy decreases 0.08% per °C from software calibration temperature.

<sup>4</sup>Expansion is used below 7 mV/div range so vertical resolution and accuracies are correspondingly reduced. Below 7mV/div full scale is defined as 56 mV.

<sup>5</sup>On time/div settings 1 μs/div and slower, bandwidth in repetitive mode is 100 MHz.

<sup>6</sup>Available over HP-IB waveform record length is:

Real-time normal: 500 points, extended: 2000 points.  
Repetitive 10 ns to 5 s/div: 1024 pts. 2 ns/div: 400 pts.  
5 ns/div: 1000 pts. 1 ns/div: 200 pts.

### HP 54502A Telecommunications Mask Template Test Option

Make telecom mask template measurements to ANSI, CCITT, and ISDN standards without using Mylar overlays. HP 54502A Option 001 automates many of the mask measurements that are time-consuming with analog oscilloscopes. Pass-fail accuracy and repeatability are improved through the use of automatic measurements, eliminating human error.

#### HP 54502A Option 001 Features

- 16 standard telecom signal mask templates stored in ROM
- Positive and negative templates
- Automatic triggering on positive "isolated ones" in live traffic for many standard telecom signals
- Automatic best-fit of test signals to positive mask templates
- Automatic pass-fail comparison of mask templates with corresponding input signals
- Automatic storage, printing or plotting of failed signals
- User-defined pass-fail tolerance
- Memory protection for user mask templates, waveforms and front panel setups

For more information on this option and a technical data sheet, contact your local HP sales office (see page 684).

<sup>1</sup>For the HP 54502A Option 001, the term "isolated ones" is defined as a pulse sequence of at least two zeroes, followed by a one, followed by at least two zeroes.

#### Ordering Information

The HP 54502A digitizing oscilloscope comes complete with two HP 10430A 10:1 1 MΩ probes, a front panel manual, a programming manual, a service manual, a power cord, and a three-year warranty.

	Price
<b>HP 54502A Digitizing Oscilloscope</b> qty 1	\$7,450
qty ≥ 2 (each)	\$7,228
<b>Opt 001 Telecommunications Mask Template Test Option</b>	+ \$500
<b>Opt 908 Rack Mount Kit (5061-6175)</b>	+ \$250
<b>Opt 910 Additional Front-Panel, Programming, and Service Manual</b>	+ \$75
<b>Opt 090 Delete Probes</b>	- \$200

☎ For off-the-shelf shipment, call 800-452-4844.